

PVC waterslang met polyester versterking Tuyau d'arrosage en PVC avec renforcement en polyester

code			L m	Ø mm	inch				min.	€
ALPHA - Nylon										
GF 80007095	vrac	8004779070952	25	15	5/8"	2,718 kg	60	1	1	25,93
GF 80007096	vrac	8004779070969	50	15	5/8"	5,350 kg	18	1	1	53,60
TRICO STAR - PVC - Anti-Torsion Hose										
GF 80007014	vrac	8004779070143	25	15	5/8"	3,974 kg	60	1	1	51,50
GF 80007015	vrac	8004779070150	50	15	5/8"	7,900 kg	30	1	1	99,00
GF 80007016	vrac	8004779070167	25	19	3/4"	5,600 kg	42	1	1	69,10
GF 80007017	vrac	8004779070174	50	19	3/4"	10,950 kg	24	1	1	139,00
BLACK STAR - Rubber / Caoutchouc - Anti-Torsion Hose										
GF 80007074	vrac	8004779008498	25	15	5/8"	3,858 kg	60	1	1	61,10
GF 80007075	vrac	8004779008504	50	15	5/8"	7,750 kg	30	1	1	123,00
GF 80007076	vrac	8004779008511	25	19	3/4"	5,650 kg	42	1	1	84,90
GF 80007077	vrac	8004779008528	50	19	3/4"	11,950 kg	24	1	1	170,00
TRICO TOP - PVC										
GF 80007021	vrac	5420000049529	100	19	3/4"	24,000 kg	30	1	1	210,00



ALPHA

5/8"

7 bar 21 bar

FREE Cadmium

TRICO STAR

5/8"

8 bar 24 bar

3/4"

7 bar 21 bar

-10°/50° UV

BLACK STAR

5/8"

12 bar 36 bar

3/4"

9 bar 27 bar

-20°/60° UV

FREE Cd-Ba-Pb

Wandbevestiging voor tuinslang Fixation murale pour tuyau

code						min.	€
GF 80007040	vrac	8004779070402	0,237 kg	-	8	1	6,15

